MAXHUB XBoard V7 Series For Microsoft Teams Rooms

Model: V865T

The MAXHUB XBoard is a Windows-based, all-in-one collaboration solution designed for meeting rooms and huddle spaces. It consists of a high-resolution 4K LCD touch display, a triple-camera system, crystal-clear speakers and a 16-microphone array. As a certified Microsoft Teams Room device, the MAXHUB XBoard offers seamless collaboration and immersive video conferencing experiences.






Professional 4K Display

High color accuracy, ∆E≤1.5 Wide color gamut, NTSC 90% Non-glare technology, 25% haze



Seamless Collaboration

Built-in touch display and Microsoft whiteboard for real-time collaboration



Triple-Camera System

Equipped with one wide-view lens and two tele-view lens to provide clear view for all room participants




Al-Powered Video Technology

Auto framing
Speaker tracking
Multi-speaker tracking
Intelligent focus



Premium Audio

Built-in 16-beamforming
microphone array,
Built-in stereo speakers
Al-powered noise reduction
Full-duplex communication



Flexible Content Share

Wired 4K content share via HDMI *
Wireless content share via wireless
dongle, MAXHUB Share app, Airplay





BYOD Mode

Plug-and-play, an accessible way to switch between Teams Rooms mode and BYOD mode



Secured and Managed

Windows 11 IOT

MAXHUB Pivot Support

V865T

Display	
Model	V865T
Screen Size (Inch)	86
Aspect Ratio	16:9
Panel	IPS
Backlight	DLED
Brightness (Typ.)	350 nits
Glass	Zero parallax 3mm thickness 9H tempered
Surface Technology	25% haze Non-glare technology
Resolution	3840 × 2160
Refresh Rate	60 Hz
Contrast Ratio	1200:1 (typ.)
Viewing Angle (H × V)	178° / 178°
Color Gamut	90% NTSC
Display Orientation	Landscape
Response Time	8 ms
Life Time	>50,000 hours
Operation Hours (Hour / Day)	16 / 7
Display Color	1.07B (10 bit)
Color Accuracy	Delta E ≤ 1.5
Sensor	Ambient light sensor Motion Sensor
Pixel Pitch	0.4935(H) × 0.4935(V) mm
Display Area	1895.04(H) × 1065.96(V) mm

Power	
Power Supply	100-240V~ 50/60Hz 5.0A
Standby Power	≤ 0.5 W
Power Consumption (Typ.)	275 W
Power Consumption (Max.)	465 W

Touch System	
Touch Technology	Intelligent Touchscreen Technology (infrared recognition)
Touch Point	50 points touch
Object Recognition Range	≥ 1.5 mm
Accuracy	± 0.5 mm
Response Time	≤ 2.5 ms
Writing Height	≤ 1 mm

Physical Specification	
Dimension (W × H × D)	1957 × 1180.1 × 103 mm
Shipping Dimension (W × H × D)	2110 × 1283 × 225 mm
Thickness of machine and wall mount	130 mm
Wall-hanging Screw Spec	M8 × 25 mm
VESA	800 × 400 mm
Net Weight	59.95 Kg
Gross Weight	74.55 Kg

Connectivity	
I/O Ports (Interactive Display)	
HDMI In (2.0) × 2	To connect an external source
USB-A 2.0 × 1	To pair with wireless dongle - WT13M / WT13S To connect keyboards or mouse, etc.
Touch (USB-B 2.0) × 1	To connect a personal laptop for BYOD mode (access to XBoard's camera & microphone)
Audio In × 1	To connect an external audio source to make XBoard a speaker
Audio Out × 1	3.5 mm mini-jack, to connect an external speaker system
RS232 × 1	9 pin
Mic In (RJ45) × 1	To connect up to a maximum of two UC BM45 as expansion speakerphones
Wireless Access Point	Yes (for wireless presentation)
Camera	
Wide Camera	50MP × 1 HFOV 86° 4x digital zoom
Telephoto Camera	50MP × 2 HFOV (combined) 72° 1.5x digital zoom
Al Features	Auto Framing Speaker Tracking Multiple-speaker Tracking Intelligent Focus

Audio	
Sound Channel	2.1
Speaker Power	2 × 10W + 20W

Microphone	
Quantity	16-mic array
Pick-up Angle	180°
Pick-up Range	Best distance – 8m / 26.2ft Maximum distance 15m / 49.2ft
Feature	Intelligent audio fence Al spatial sound AEC (Auto echo cancellation) ANC (Al noise cancellation) AGC (Auto gain control)

Environmental Conditions	
Operating Temperature	0°C~40°C
Storage Temperature	-20°C~60°C
Operating Humidity	10%~90% RH
Storage Humidity	10%~90% RH
Altitude	Below 5000 meters

PC Module (Slot-in, included in the package)	
CPU	12th gen Intel Core i5 – 1240p
GPU	Intel® Iris® Xe Graphics eligible
Memory	16GB DDR4 (8GB x2)
Storage	256GB SSD (M.2)
Operating system	Windows 11 IOT
TPM 2.0	Yes
Inputs & Outputs	USB-A 3.0 x3
	HDMI In (2.0) x1 *
	(Content share in Teams Rooms mode)
	HDMI Out × 2
	(Only for screen mirroring)
	RJ45 × 1 (Ethernet)
	RJ45 × 1
	(For optional touch console – TCP30T)
Wi-Fi	Wi-Fi 6
Bluetooth	Bluetooth 5.1

Accessory (included in the package)	
Wireless Module	(AP)
HDMI Cable (3 m / 9.8 ft)	× 1
Power Cord	× 1
Passive Stylus	× 2
Wall mounts kits	× 1
Certification	
Safety	IEC 62368-1
EMC	Class B

Statement

^{*} NOTE: HDMI In x 1 (content share in Teams Rooms mode): Available in Q4 2024.

Please note that the size and weight may vary by configuration and manufacturing process. For accurate product specifications, please refer to the actual product.

Product images are for reference only and may differ slightly from the actual product in appearance, color, size, etc.

The description, illustrations, etc. in this document may be subject to change in accordance with the latest product specification and performance.

Should any changes be necessary, the document may be updated without written notice.